



SPECIFICATION

Input Voltage [V]	220-240VAC
Output Voltage [V]	72VDC 72mA 50/60HZ
Operating frequency [KHz]	>40
Lamp Wattage [W]	4W&6W Switch changeable
Operating Wattage [W]	6.2W Max
LED BRAND	Bridgelux LEDS SMD
Lumen output [lm]	400lm (+10%/-15%)
MAX Luminous Intensity (CD)	100 lux at 2m Height
Power Factor	0.8
Beam angle	from 10° to 120°
CCT(K)	4CCT 2200K-2700K-4000K-Dim To Warm(2200K-3000K)
Dimmable	Triac Dimmable
Size (mm)	L100xW100xH100mm
Material	ALUMINUM HOUSING
Operating temp range (°C)	-30 to +45 °C
Humidity	10%-50%
Warranty	3 Years
Equal light	35W CFL
WEIGHT(KGS)	0.45
PCS/CTN	50
CTN SIZE (CM)	52*42*23.5
Package	white box +netural packing

Product Features

- . Beam angle Ajustable from 10°to 120°
- . CCT 2200-2700-4000K Changeable and 3000-2000K Dim To Warm
- . 4W & 6W powerful Switch Changeable
- . Triac Dimmable from 5%-100%
- . Impressive 25,000 hours lamp life reduces re-lamping costs
- . IP65 ,Matt White / Matt black available

